

NU305HRV PRODUCT INFORMATION SHEET

CORE

Polypropylene crossflow core. Nu-Air part #PC1414A. Dimensions: 14" L x 14" W x 14H".

ELECTRICAL

115Volt, 60Hz, 170Watts. Supplied with 4FT power cord. Unit FLA: 1.9 Amps MCA: 1.9 Amps MOCP: 15

MOTORS

Fractional 2 speed PSC motors. 1275RPM. Nu-Air Part #50104. Independent speed adjustment of either supply or exhaust motor in both high and low speed.

BLOWERS

Two forward curve, dual inlet fans using permanently sealed bearings.

CABINET

The case is constructed of .050 pre-painted white aluminum that is fully insulated with 1" foil faced fibreglass insulation. Drain connections are 1/2"(2). Nu-Air drain fitting part #50362. Cabinet Dimensions: 36" L x 23" H x 17" W. Duct Connection Size: 8" Oval.

CONFIGURATION

Available in standard 'C' or reverse 'G' configuration. See drawings.

ELECTRONICS

Integrated microprocessor. Built in interlock contacts. 24V circuit protection with self resetting fuse. 12VDC and/or 24V connection for remote control with mechanical switch or any Nu-Air control.

DEFROST OPTIONS

Model **NU305FP** – Supply fan shuts down while exhaust air defrosts core.
Model **NU305DP** – Bypass damper routes indoor air to defrost core.

WEIGHT – 50lbs/23kg


SHIPPING WEIGHT – 70lbs/32kg

FILTERS



2 Filters @ 13.5" x 14". Washable MERV6 mesh filters in supply and exhaust airstreams. 1" pleated MERV8 or MERV13 filter upgrade available upon request.

Filter	Type	Part #	Qty
MERV6	½" Polyester Mesh	50938	1 Set
MERV8	1" Pleated	50810	2
MERV13	1" Pleated	50811	2

NOMENCLATURE EXAMPLE



Distributed by:



CONTROL OPTIONS

12 VDC controls available


Lumina (NAV-561) - Digital wall mounted control c/w Dehumidistat, timer functions & filter change indicator

24 V controls available


- NAV-460** - 20/40/60 minute timer
- Dstat-1** - Humidity control
- WIN-1** – Humidity control c/w Off/Standby/Continuous/Intermittent
- WIN-20** – 20 minute push button timer (up to 6 per unit)
- Any dry contact switch** – By Others

WARRANTY - Provided installation is in accordance with instruction, 15 year warranty on the HRV core and a 2 year warranty on replacement parts.

NU305 CONFIGURATION DRAWINGS



1 - OUTSIDE AIR / FRESH AIR FROM OUTSIDE	2 - SUPPLY AIR / FRESH AIR TO SPACE	3 - RETURN AIR / EXHAUST AIR FROM SPACE	4 - EXHAUST AIR / EXHAUST AIR TO OUTSIDE	5 - DEFROST AIR (OPTIONAL - DP/DL MODELS ONLY)
--	-------------------------------------	---	--	--



In the interest of product improvement, Nu-Air reserves the right to change specifications without notice.